

ASSEMBLY INSTRUCTIONS

Liscia Small Flush Mount



Item # ARN 4170

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

TOOLS REQUIRED (NOT INCLUDED):

Phillips Screwdriver Slotted Screwdriver



- Carefully remove all parts from the box. Place on a clean, soft surface.
- Remove mounting plate **(B)** from canopy **(E)** by removing threaded caps **(F)**.
- Install mounting plate **(B)** to the junction box and secure with mounting screws **(D)**.
- Run support cable through hole on back of mounting plate **(B)**. Loosen cable lock and install to end of support cable. Insert cable through the other side of cable lock and tighten ends with a screwdriver to secure. (see diagram 1)
- Wrap fixture ground wire (bare copper) around the green grounding screw (see diagram 1). Tighten. Continue fixture ground wire and connect to supply ground wire (usually green or bare copper) using wire nut **(A)**.


NOTE: It is imperative that the fixture is grounded.

- Connect fixture neutral wire (white) to the supply neutral wire (usually white) using wire nut **(A)**.
- Connect fixture hot wire (black) to the supply hot wire (usually black) using the wire nut **(A)**.


CAUTION: Do not reverse the hot and neutral connections.

- Make sure all wire connections are tight, then carefully tuck into the junction box.
- Install canopy **(E)** to mounting plate **(B)** and secure with threaded caps **(F)**.


ASSEMBLY INSTRUCTIONS



Layer 3



Layer 2



Layer 1

Liscia Small Flush Mount

Item # ARN 4170

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

10. Install light bulbs into sockets.

Crystal Assembly - Use diagrams labeled Layer 1 - Layer 3 to complete crystal assembly below:

1. Hang crystals **(I)** to bottom ring (Layer 1) and secure using provided pliers.
2. Hang the rest of crystals **(I)** to medium ring (Layer 2) and secure using provided pliers.
3. Hang crystals **(H)** onto top ring (Layer 1) and secure using provided pliers.
4. Hang crystals **(G)** to threaded nipples **(L)** from bottom (Layer 1) and working your way to the top (layer 3) as shown in figures. Secure using provided pliers.

Care Instructions: Clean only with a soft dry cloth or feather duster. Do not use abrasive or chemical agents.